CYCRAFT

SEGA®

SERVICE BULLETIN

December 15th, 2006

GAME NAME: CYCRAFT (INITIAL D3, CLUB KART)

SUBJECT: • ERROR "SMCP: BROKEN CONNECTION' DISPLAY ON MONITOR

THERE IS MISS COMMUNICATION BETWEEN NAOMI BOARD (INITIAL D3 GAME) AND SMCP (MAIN PCB OF CYCRAFT CABINET).

PLEASE REFER BELOW TO CHECK IP ADDRESS SETTING IN NAOMI BOARD.
(REFER PAGE 16 OF INITIAL D3 MANUAL)

1) PRESS "TEST SW" ON CYCRAFT CABINT TO GO TO SYSTEM MENU.
2) GO TO "NETWORK SETTING."
3) SET UP EACH CONTENTS AS BELOW.

NOTE: NOT "1" PLEASE SET UP "2"

NETWORK TYPE: ETHER
REMOTE: DISABLE
IP ADDRESS: 192. 168. 1. 2
NET MASK: 255.255.255.0

4) YOU WILL SEE LETTER OF "SET" NEXT RIGHT OF IP ADDRESS AND NET MASK.
   PLEASE SELECT "SET" THEN PRESS TEST SWITCH TO UPDATED YOUR CHANGES.